

COE512CRB1X

5MP Network IR Turret Camera

VISION





Features

- 5MP (2592 × 1944) H.265 full real time coding
- Max. resolution: 2592 × 1944
- ICR auto switch, true day / night
- 30 ~ 50m IR night view distance
- 1Ch built-in MIC
- DC12V/PoE power supply
- IP67 ingress protection
- Triple stream
- 2.8 - 12mm Motorized zoom

SPECIFICATIONS

CAMERA		FUNCTIONS	
Image Sensor	1 / 2.7" CMOS	Remote Monitoring	Web browsing, CMS remote control
Image Size	2592 x 1944	Online Connection	Support simultaneous monitoring for up to 4 users; Support multi-stream real time transmission
Electronic Shutter	1 / 25 s ~ 1 / 100000 s	Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS
Iris Type	Fixed Iris	Interface Protocol	ONVIF, GB-T/28181-2011
Min. Illumination	0.0236 lux@2.0, AGC ON; 0 lux with IR 0.0085 lux@F1.2, AGC ON; 0 lux with IR	Storage	Network remote storage
Lens	2.8~12mm@F1.4, motorized zoom lens Horizontal field of view:90.5°~32.9°	Smart Alarm	Motion detection
Wide Dynamic Range	Digital WDR	General	Watermark, IP address filtering, video mask, heartbeat, password protection
BLC/HLC	Yes	MISCELLANEOUS	
Defog	Yes	Power Supply	DC12V/PoE
Digital NR	3D DNR	Power Consumption	< 10W
Angle Adjustment	Pan: 0°~360°; Tilt: 0°~80°; Rotation: 0°~360°	IR Distance	30 ~ 50 m
IMAGE		Ingress Protection	IP67
Video Compression	H.265 / H.264	Operating Environment	- 30 °C ~ 60 °C (-22°F~140°F) Humidity: less than 95 % (non-condensing)
H.264 Compression Standard	Main Profile@Leve4.1 High Tier	Weight	Approx. 1.4lbs (0.64KG)
Resolution	5MP (2592 x 1944), 4MP (2560 x 1440), 1080P (1920 x 1080), 720P (1280 x 720), D1, CIF, VGA	ORDERING INFORMATION	
Main Stream	5MP (1-20fps)/4MP (1-30fps)/1080P (1-30fps)/720P (1-30fps)	COE512CRB1X	5MP Network IR Water-Proof Dome Camera
Sub Stream	720P (1~15fps)/D1(1~30fps)/CIF (1~30fps)		
Third Stream	D1/CIF/480x240 (1~30fps);50HZ: D1/CIF/480x240 (1~25fps)		
Bit Rate	64 Kbps ~ 5 Mbps		
Bit Rate Type	VBR / CBR		
Audio Compression	G711A / U		
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR,etc. adjustable through client software or web browser		
ROI	Each ROI to be configured separately		
INTERFACES			
Network	RJ45		
Video Output	No		
Audio	1CH built-in MIC		
Alarm	No		
Storage	No		



Make the Intelligent Choice

For more information about PM Tronics Security products, to see demonstrations, or to discuss your company's needs contact the PMT team at 727-786-1900.