MORPHOACCESS® SIGMA LITE SERIES

SLIM AND POWERFUL FINGERPRINT ACCESS TERMINALS





- World's #1 fingerprint technology inside 1:10,000 user identification in 1 second
- High capacity
- 250,000 users (1:1), 10,000 users (1:N), 1 Million logs Anti-fraud features
 - Fake finger detection, duress finger, timed anti-pass back
- Flexibility Prox[®], iClass[®] or MIFARE[®]/DESFire[®]/NFC contactless card reader as an option
- Tough design Weather (IP65) and vandal (IK08) resistant



Motor Compatible with svicinon incestigned to set

MORPHOACCESS® SIGMA LITE SERIES SLIM AND POWERFUL FINGERPRINT ACCESS TERMINALS

The SIGMA family welcomes new members!

Engineered with the same attention to detail and performance as their predecessor, the MorphoAccess® SIGMA Lite terminals are specifically designed to equip narrow mounting surfaces, such as glass/aluminum door mullions, turnstiles, or server rack doors. With two designs and multiple card reader options, there

are a variety of models to address the widest range of deployment scenarios, both indoors and outdoors.

World's #1 fingerprint technology inside -

- Latest generation Morpho embedded algorithms (MINEX and FIPS 201 approved)
- Up to 250,000 users in 1:1 verification mode
- Up to 10,000 users (30,000 templates) in 1:N identification mode
- 1:10,000 user matching in 1 second
- Accuracy maintained regardless of number of users in database
- FBI PIV IQS certified optical sensor

Full set of card reader options

- Prox[®]
- iClass[®]
- MIFARE[®]/MIFARE[®] Plus/DESFire[®]/NFC



MA SIGMA Lite With blue/green/red LED indicator and buzzer

BUILT FOR THE REAL WORLD

WEATHER AND VANDAL⁽¹⁾ **RESISTANT BY DESIGN**



EASY INSTALLATION AND MAINTENANCE



COMPATIBLE WITH EXISTING INSTALLATIONS

> Morpho and bioscrypt

 Using MorphoManager application or MIK SDK on a Morpho network Using SecureAdmin application or SecureSDK on a Bioscrypt network

- **CPU:** ARM[®] Cortex[™]-A9 core 1GHz
- Linux Operating System
- FBI PIV IQS certified optical fingerprint sensor
- Contactless reader options: Prox[®], iClass[®], MIFARE[®]/MIFARE[®] Plus/DESFire[®]/NFC
- Network/Communication:
- Ethernet, RS485, USB
- Wi-Fi option
- Power supply: - 12V-24V DC
- Power over Ethernet (PoE)

 Internal storage capacity: 512MB Flash, 512MB RAM - 1:N mode: 3,000 user records, extendable to 10,000 with license (*3 templates each, including 1 duress) - 1:1 mode: 250,000 user IDs

Ð

Ð

- 1 Million transaction logs

• Inputs/outputs: Wiegand In & Out (customizable up to 512 bits), Door Relay, 2 General Purpose Inputs (including Door monitoring), 2 General Purpose Outputs

- Tamper switches
- (1) IK08 rating is not available for MA SIGMA Lite+ design
- ⁽²⁾ Alternate password solution instead of fingerprints
- ⁽³⁾ Prevents repeated authorizations by the same user, within a configurable time period

With 2.8" OVGA color

touchscreen and buzzer



- Time & Attendance In & Out function keys
- User ID, PIN and BioPIN⁽²⁾ management
- Intuitive icons and live messages

Anti-fraud features

- Fake finger detection
- Duress finger
- Timed anti-pass back function⁽³⁾
- Banned/authorized user lists

The SIGMA family



- Operating conditions:
- Temperature: -20°C to 55°C (-4°F to 131°F)
- Humidity: 10% to 80% (non condensing)
- Ingress protection: IP65
- Mechanical impact protection: IK08⁽¹⁾
- **HxWxD** = 156*68*62 mm (6.14*2.68*2.44 inches)
- Weight: 280 grams
- EMC/Safety standards: CE, CB, FCC
- RoHS, REACh and WEEE compliant

KEY MISSIONS, KEY TECHNOLOGIES, KEY TALENTS



Morpho